



VidyoRoom HD-2C™

High Performance Group Collaboration

Business Challenge

Today's workplace requires high quality video group collaboration to maintain a competitive edge. High quality video collaboration was cost prohibitive to deploy for broader use, forcing enterprises to choose between high quality for a few, or low quality for the masses. Enterprises require group video conferencing systems that deliver crystal clear quality that can be broadly deployed for maximum effect.

VidyoRoom HD-2C delivers impressive quality for every meeting room

Quality matters.

Solution Overview

The rapid pace of business demands clear communications so teams can make decisions quickly. The best way to maintain a nimble organization is to clearly communicate important ideas the first time. Not all meetings can be an in-person, but high-quality video conferencing is the next best thing to an in-person meeting.

Fast paced teams demand high quality video conferencing to ensure no detail is lost. The powerful VidyoRoom™ HD-2C is the ideal system for team collaboration with seamless touch screen support and the ability to deliver incredible 4K Ultra HD video resolution without sacrificing quality from remote participants or their content.

The VidyoRoom HD-2C is very affordable and has a compact form factor that is easy to deploy in virtually any conference room.

Outstanding User Experience

- Receive up to 4K video and content
- Dynamic adaptation technology continuously optimizes the video for unmatched fidelity, even on wireless
- Screen configurations supporting up to 16 participants viewable on screen
- Multipoint Content Sharing: toggle to switch between shares from multiple participants
- Calendar integration for single-tap meeting access with support for Microsoft® Exchange and Google® Calendar
- Enable a video wall system by pairing multiple VidyoRoom systems. Display limitless video windows of remote participants.
- Meet with participants from all types of endpoints, including room systems, desktops, laptops, tablets, and mobile devices

IT Benefits

- Compatible with VidyoPlatform's hosted video service as well as on-premises based systems
- Multiple user friendly remote control options including room automation systems like AMX® and Crestron®, the free VidyoControl app for tablets or hand-held remote control with simple to navigate on-screen UI
- Tight integration with professional audio and USB PTZ Logitech® GROUP
- Conference moderation and automatic software updates
- Advanced SVC (UCIF Mode 2s) delivers unmatched quality, reliability and efficiency
- Flexible deployment options supporting one and two screen configuration

VidyoRoom HD-2C Specifications

Screen Configurations	Single Monitor: 4K Ultra HD at 30 fps (Up to 8 viewable participants, Configurable layouts for participant video and content) Dual Monitor: 1080p at 60 fps (Up to 12 viewable participants, Configurable layouts for participant video and content)
Video Codec	Native: H.264 SVC (UCIF Mode 2s), VP9 SVC, VP8 Via VidyoGateway: H263, H264 AVC
Audio Codec	Native: OPUS, SPEEX Wideband Audio, up to 32 KHz sampling rate Via VidyoGateway: G.711, G.722
Live Resolutions (Transmitted)	1080p60, 1080p30, 720p60, 720p30, 540p30, 450p30, 360p30
Live Resolutions (Received)	4K/ 2160p30, 1080p60, 1080p30, 1080p15, 720p60, 720p30, 540p30, 450p30, 360p30
Max Data Rate	Transmit: Up to 6Mbps Receive: Up to 6Mbps
Content Sharing	Content In: 1 x USB (Video+Audio, Up to 1080p30p with DVI/HDMI to USB3 accessory) Resolutions: 1080p30, 720p30 Remote Display: Scales shared content from remote participants (up to 2160p) to screen resolution Multipoint Content Sharing: Toggle to switch between shares from multiple remote participants
Video Outputs	1 X HDMI 2.0, 1 x mDP (Mini Display Port to HDMI 1.4 adapter included)
Camera In	Standard: 1 x USB3.2 (Supported DVI/HDMI cameras can be connected using an DVI/HDMI to USB3 accessory).
Camera Control	1 x USB3.2 using USB to serial port adapter (Included)
Audio Inputs/Outputs	USB
Control	IR remote control, VidyoControl app on iOS & Android, remote control API with support for Crestron and AMX, and mouse & keyboard (Healthcare edition)
Signaling Protocols	EMCP, SCIP
Calendar Support	Microsoft® Exchange and Google® Calendar
Encryption	AES 256-bit, TLS, SRTP, HTTPS
Monitoring	SNMP
Network Interface	One onboard GbE port via integrated gigabit ethernet intel i219LM, supports Wakeon-LAN Optional PCIe ethernet adapters are available.
Languages	English, Chinese (Simplified or Traditional), Finnish, French, German, Italian, Japanese, Korean, Norwegian, Polish, Portuguese, Russian, Spanish, Swedish, Thai, Turkish
Power Supply	170W-230W power adapter, 100-240V, 89% PSU
Environment	Operating Temperature Range: 50 to +95 °F (10 to 35°C) Non-Operating Temperature Range: -40 to 140°F (-40 to 60°C)
Safety	NRTL Tested for Safety to the following Standard: UL 60950-1, 2nd Edition, 2014-10-14 (Information Technology Equipment -Safety - Part 1: General Requirements) CAN/CSA C22.2 No. 60950-1-07, 2nd Edition, 2014-10 (Information Technology Equipment- Safety - Part 1: General Requirements) Including the following additional standards: EN 60950-1:2006 + A11:2009 + A1:2010 + A12:2011 + A2:2013 (which includes all European national differences)
Regulatory:	FCC (US), ICES (Canada), CE (EU), AS/NZS (Australia/New Zealand), CCC (China), EAC (Russia), BSMI(Taiwan), MSIP (Korea)
Dimensions	Height: 7.0 in" (179mm) Width: 1.5 in" (37mm) Depth: 7.2 in" (182.9mm) Gross Weight: 3 lbs (1.4 Kg)
Options	VidyoRoom HD-2C Endpoint only VidyoRoom HD-2C Bundle includes VidyoRoom HD-2C, Logitech GROUP, Inogeni DVI to USB
Operating System:	Windows 10 IoT